

Search

A to Z Index |En Español |Contact Us |FAQs | About OSHA

OSHANewsletter RSS Feeds

Menu

Occupational Safety & Health Administration We Can Help

G Regulations (Standards - 29 CFR) - Table of Contents

• **Part Number:** 1910

• Part Title: Occupational Safety and Health Standards

• Subpart:

• **Subpart Title:** Hazardous Materials

• Standard Number: 1910.119

• **Title:** Process safety management of highly hazardous chemicals.

• Appendix: A, B, C, D

Purpose. This section contains requirements for preventing or minimizing the consequences of catastrophic releases of toxic, reactive, flammable, or explosive chemicals. These releases may result in toxic, fire or explosion hazards.

1910.119(a)

Application.

1910.119(a)(1)

This section applies to the following:

1910.119(a)(1)(i)

A process which involves a chemical at or above the specified threshold quantities listed in Appendix A to this section;

1910.119(a)(1)(ii)

A process which involves a Category 1 flammable gas (as defined in 1910.1200(c)) or a flammable liquid with a flashpoint below 100 °F (37.8 °C) on site in one location, in a quantity of 10,000 pounds (4535.9 kg) or more except for:

1910.119(a)(1)(ii)(A)

Hydrocarbon fuels used solely for workplace consumption as a fuel (e.g., propane used for comfort heating, gasoline for vehicle refueling), if such fuels are not a part of a process containing another highly hazardous chemical covered by this standard;

1910.119(a)(1)(ii)(B)

Flammable liquids with a flashpoint below 100 °F (37.8 °C) stored in atmospheric tanks or transferred which are kept below their normal boiling point without benefit of chilling or refrigeration.

1910.119(a)(2)

This section does not apply to:

1910.119(a)(2)(i)

Retail facilities;

1910.119(a)(2)(ii)

Oil or gas well drilling or servicing operations; or,

1910.119(a)(2)(iii)

Normally unoccupied remote facilities.

1910.119(b)

Definitions.

Atmospheric tank means a storage tank which has been designed to operate at pressures from atmospheric through 0.5 p.s.i.g. (pounds per square inch gauge, 3.45 Kpa).

Boiling point means the boiling point of a liquid at a pressure of 14.7 pounds per square inch absolute (p.s.i.a.) (760 mm.). For the purposes of this section, where an accurate boiling point is unavailable for the material in question, or for mixtures which do not have a constant boiling point, the 10 percent point of a distillation performed in accordance with the Standard Method of Test for Distillation of Petroleum Products, ASTM D-86-62, which is incorporated by reference as specified in Sec. 1910.6, may be used as the boiling point of the liquid.

Catastrophic release means a major uncontrolled emission, fire, or explosion, involving one or more highly hazardous chemicals, that presents serious danger to employees in the workplace.

Facility means the buildings, containers or equipment which contain a process.

Highly hazardous chemical means a substance possessing toxic, reactive, flammable, or explosive properties and specified by paragraph (a)(1) of this section.

Hot work means work involving electric or gas welding, cutting, brazing, or similar flame or spark-producing operations.

Normally unoccupied remote facility means a facility which is operated, maintained or serviced by employees who visit the facility only periodically to check its operation and to perform necessary operating or maintenance tasks. No employees are permanently stationed at the facility. Facilities meeting this definition are not contiguous with, and must be geographically remote from all other buildings, processes or persons.

Process means any activity involving a highly hazardous chemical including any use, storage, manufacturing, handling, or the on-site movement of such chemicals, or combination of these activities. For purposes of this definition, any group of vessels which are interconnected and separate vessels which are located such that a highly hazardous chemical could be involved in a potential release shall be considered a single process.

Replacement in kind means a replacement which satisfies the design specification.

Trade secret means any confidential formula, pattern, process, device, information or compilation of information that is used in an employer's business, and that gives the employer an opportunity to obtain an advantage over competitors who do not know or use it. See Appendix E to § 1910.1200—Definition of a Trade Secret (which sets out the criteria to be used in evaluating trade secrets).

1910.119(c)

Employee participation.

1910.119(c)(1)

Employers shall develop a written plan of action regarding the implementation of the employee participation required by this paragraph.

1910.119(c)(2)

Employers shall consult with employees and their representatives on the conduct and development of process hazards analyses and on the development of the other elements of process safety management in this standard.

1910.119(c)(3)

Employers shall provide to employees and their representatives access to process hazard analyses and to all other information required to be developed under this standard.

1910.119(d)

Process safety information. In accordance with the schedule set forth in paragraph (e)(1) of this section, the employer shall complete a compilation of written process safety information before conducting any process hazard analysis required by the standard. The compilation of written process safety information is to enable the employer and the employees involved in operating the process to identify and understand the hazards posed by those processes involving highly hazardous chemicals. This process safety information shall include information pertaining to the hazards of the highly hazardous chemicals used or produced by the process, information pertaining to the equipment in the process.

1910.119(d)(1)

Information pertaining to the hazards of the highly hazardous chemicals in the process. This information shall consist of at least the following:

1910.119(d)(1)(i)

Toxicity information;

1910.119(d)(1)(ii)

Permissible exposure limits;

1910.119(d)(1)(iii)

Physical data;

1910.119(d)(1)(iv)

Reactivity data:
1910.119(d)(1)(v)
Corrosivity data;
1910.119(d)(1)(vi) Thermal and chemical stability data; and
Thermal and chemical stability data; and
1910.119(d)(1)(vii)
Hazardous effects of inadvertent mixing of different materials that could foreseeably occur.
Note: Safety data sheets meeting the requirements of 29 CFR 1910.1200(g) may be used to comply with this requirement to the extent they contain the
information required by this subparagraph.
1910.119(d)(2)
Information pertaining to the technology of the process.
1910.119(d)(2)(i)
Information concerning the technology of the process shall include at least the following:
1910.119(d)(2)(i)(A) A block flow diagram or simplified process flow diagram (see Appendix B to this section);
2.52 a.a.g. a.m o. o.mp.inea process non alagram (see Appendix b to allo section))
1910.119(d)(2)(i)(B)
Process chemistry;
1910.119(d)(2)(i)(C)
Maximum intended inventory;
1910.119(d)(2)(i)(D)
Safe upper and lower limits for such items as temperatures, pressures, flows or compositions; and,
1910.119(d)(2)(i)(E) An evaluation of the consequences of deviations, including those affecting the safety and health of employees.
An evaluation of the consequences of deviations, including those affecting the safety and fleatin of employees.
1910.119(d)(2)(ii)
Where the original technical information no longer exists, such information may be developed in conjunction with the process hazard analysis in sufficient detail to support the analysis.
1910.119(d)(3)
Information pertaining to the equipment in the process.
1910.119(d)(3)(i) Information pertaining to the equipment in the process shall include:
1910.119(d)(3)(i)(A) Matarials of construction:
Materials of construction;
1910.119(d)(3)(i)(B)
Piping and instrument diagrams (P&ID's);
1910.119(d)(3)(i)(C)
Electrical classification;
1910 11974)(3)(i)(D)
1910.119(d)(3)(i)(D) Relief system design and design basis;
1910.119(d)(3)(i)(E) Ventilation system decign:
Ventilation system design;
1910.119(d)(3)(i)(F)
Design codes and standards employed;
1910.119(d)(3)(i)(G)

Material and energy balances for processes built after May 26, 1992; and,
1910.119(d)(3)(i)(H)
Safety systems (e.g. interlocks, detection or suppression systems).
1910.119(d)(3)(ii) The employer shall document that equipment complies with recognized and generally accepted good engineering practices.
The employer shall document that equipment complies with recognized and generally accepted good engineering practices.
1910.119(d)(3)(iii)
For existing equipment designed and constructed in accordance with codes, standards, or practices that are no longer in general use, the employer shall determine and document that the equipment is designed, maintained, inspected, tested, and operating in a safe manner.
1910.119(e)
Process hazard analysis.
1910.119(e)(1) The employer shall perform an initial process hazard analysis (hazard evaluation) on processes covered by this standard. The process hazard analysis shall
be appropriate to the complexity of the process and shall identify, evaluate, and control the hazards involved in the process. Employers shall determine and document the priority order for conducting process hazard analyses based on a rationale which includes such considerations as extent of the process hazards, number of potentially affected employees, age of the process, and operating history of the process. The process hazard analysis shall be conducted as soon as possible, but not later than the following schedule:
1910.119(e)(1)(i)
No less than 25 percent of the initial process hazards analyses shall be completed by May 26, 1994;
1910.119(e)(1)(ii)
No less than 50 percent of the initial process hazards analyses shall be completed by May 26, 1995;
1910.119(e)(1)(iii)
No less than 75 percent of the initial process hazards analyses shall be completed by May 26, 1996;
1910.119(e)(1)(iv)
All initial process hazards analyses shall be completed by May 26, 1997.
1910.119(e)(1)(v)
Process hazards analyses completed after May 26, 1987 which meet the requirements of this paragraph are acceptable as initial process hazards analyses. These process hazard analyses shall be updated and revalidated, based on their completion date, in accordance with paragraph (e)(6) of this standard.
1910.119(e)(2)
The employer shall use one or more of the following methodologies that are appropriate to determine and evaluate the hazards of the process being
analyzed.
1910.119(e)(2)(i)
What-If;
1910.119(e)(2)(ii) Checklist;
CHECKIST
1910.119(e)(2)(iii)
What-If/Checklist;
1910.119(e)(2)(iv)
Hazard and Operability Study (HAZOP);
1910.119(e)(2)(v) Failure Mode and Effects Analysis (FMEA);
i dilate mode and Effects Alialysis (FPLA),
1910.119(e)(2)(vi)
Fault Tree Analysis; or
1910.119(e)(2)(vii)
An appropriate equivalent methodology.
1910.119(e)(3)

The process hazard analysis shall address:
1910.119(e)(3)(i)
The hazards of the process;
1910.119(e)(3)(ii)
The identification of any previous incident which had a likely potential for catastrophic consequences in the workplace;
1910.119(e)(3)(iii) Engineering and administrative controls applicable to the hazards and their interrelationships such as appropriate application of detection methodologies to
provide early warning of releases. (Acceptable detection methods might include process monitoring and control instrumentation with alarms, and detection
hardware such as hydrocarbon sensors.);
1910.119(e)(3)(iv)
Consequences of failure of engineering and administrative controls;
1010 110/2/2/()
1910.119(e)(3)(v) Facility siting;
1910.119(e)(3)(vi) Human factors; and
Tiulian factors, and
1910.119(e)(3)(vii)
A qualitative evaluation of a range of the possible safety and health effects of failure of controls on employees in the workplace.
1910.119(e)(4)
The process hazard analysis shall be performed by a team with expertise in engineering and process operations, and the team shall include at least one
employee who has experience and knowledge specific to the process being evaluated. Also, one member of the team must be knowledgeable in the specific process hazard analysis methodology being used.
1910.119(e)(5)
The employer shall establish a system to promptly address the team's findings and recommendations; assure that the recommendations are resolved in a timely manner and that the resolution is documented; document what actions are to be taken; complete actions as soon as possible; develop a written
schedule of when these actions are to be completed; communicate the actions to operating, maintenance and other employees whose work assignments are
in the process and who may be affected by the recommendations or actions.
1910.119(e)(6)
At least every five (5) years after the completion of the initial process hazard analysis, the process hazard analysis shall be updated and revalidated by a team
meeting the requirements in paragraph (e)(4) of this section, to assure that the process hazard analysis is consistent with the current process.
1910.119(e)(7)
Employers shall retain process hazards analyses and updates or revalidations for each process covered by this section, as well as the documented resolution of recommendations described in paragraph (e)(5) of this section for the life of the process.
of recommendations described in paragraph (e)(3) of this section for the life of the process.
1910.119(f)
Operating procedures.
1910.119(f)(1)
The employer shall develop and implement written operating procedures that provide clear instructions for safely conducting activities involved in each
covered process consistent with the process safety information and shall address at least the following elements.
1910.119(f)(1)(i)
Steps for each operating phase:
1910.119(f)(1)(i)(A)
Initial startup;
1910.119(f)(1)(i)(B)
Normal operations;
1910.119(f)(1)(i)(C) Temporary operations;
Temporary operations,
1910.119(f)(1)(i)(D)

Emergency shutdown including the conditions under which emergency shutdown is required, and the assignment of shutdown responsibility to qualified operators to ensure that emergency shutdown is executed in a safe and timely manner.
1910.119(f)(1)(i)(E)
Emergency Operations;
1910.119(f)(1)(i)(F)
Normal shutdown; and,
4040 410/5V4V6V
1910.119(f)(1)(i)(G) Startup following a turnaround, or after an emergency shutdown.
Suitab following a cartarouna, or after all emergency shadown.
1910.119(f)(1)(ii)
Operating limits:
1910.119(f)(1)(ii)(A)
Consequences of deviation; and
1910.119(f)(1)(ii)(B)
Steps required to correct or avoid deviation.
1910.119(f)(1)(iii)
Safety and health considerations:
4040 440(E)(4)(***)(A)
Properties of, and hazards presented by, the chemicals used in the process;
Troperacs of, and nazards presented by, the chemicals used in the process,
1910.119(f)(1)(iii)(B)
Precautions necessary to prevent exposure, including engineering controls, administrative controls, and personal protective equipment;
1910.119(f)(1)(iii)(C)
Control measures to be taken if physical contact or airborne exposure occurs;
1910.119(f)(1)(iii)(D)
Quality control for raw materials and control of hazardous chemical inventory levels; and,
1910.119(f)(1)(iii)(E)
Any special or unique hazards.
1910.119(f)(1)(iv)
Safety systems and their functions.
1910.119(f)(2)
Operating procedures shall be readily accessible to employees who work in or maintain a process.
1910.119(f)(3)
The operating procedures shall be reviewed as often as necessary to assure that they reflect current operating practice, including changes that result from
changes in process chemicals, technology, and equipment, and changes to facilities. The employer shall certify annually that these operating procedures are current and accurate.
current and accurate.
1910.119(f)(4)
The employer shall develop and implement safe work practices to provide for the control of hazards during operations such as lockout/tagout; confined space
entry; opening process equipment or piping; and control over entrance into a facility by maintenance, contractor, laboratory, or other support personnel. These safe work practices shall apply to employees and contractor employees.
1910.119(g)
Training.
-
1910.119(g)(1)
Initial training.
1910.119(g)(1)(i)

Each employee presently involved in operating a process, and each employee before being involved in operating a newly assigned process, shall be trained in an overview of the process and in the operating procedures as specified in paragraph (f) of this section. The training shall include emphasis on the specific safety and health hazards, emergency operations including shutdown, and safe work practices applicable to the employee's job tasks.

1910.119(g)(1)(ii)

In lieu of initial training for those employees already involved in operating a process on May 26, 1992, an employer may certify in writing that the employee has the required knowledge, skills, and abilities to safely carry out the duties and responsibilities as specified in the operating procedures.

1910.119(g)(2)

Refresher training. Refresher training shall be provided at least every three years, and more often if necessary, to each employee involved in operating a process to assure that the employee understands and adheres to the current operating procedures of the process. The employer, in consultation with the employees involved in operating the process, shall determine the appropriate frequency of refresher training.

1910.119(g)(3)

Training documentation. The employer shall ascertain that each employee involved in operating a process has received and understood the training required by this paragraph. The employer shall prepare a record which contains the identity of the employee, the date of training, and the means used to verify that the employee understood the training.

1910.119(h)

Contractors.

1910.119(h)(1)

Application. This paragraph applies to contractors performing maintenance or repair, turnaround, major renovation, or specialty work on or adjacent to a covered process. It does not apply to contractors providing incidental services which do not influence process safety, such as janitorial work, food and drink services, laundry, delivery or other supply services.

1910.119(h)(2)

Employer responsibilities.

1910.119(h)(2)(i)

The employer, when selecting a contractor, shall obtain and evaluate information regarding the contract employer's safety performance and programs.

1910.119(h)(2)(ii)

The employer shall inform contract employers of the known potential fire, explosion, or toxic release hazards related to the contractor's work and the process.

1910.119(h)(2)(iii)

The employer shall explain to contract employers the applicable provisions of the emergency action plan required by paragraph (n) of this section.

1910.119(h)(2)(iv)

The employer shall develop and implement safe work practices consistent with paragraph (f)(4) of this section, to control the entrance, presence and exit of contract employers and contract employees in covered process areas.

1910.119(h)(2)(v)

The employer shall periodically evaluate the performance of contract employers in fulfilling their obligations as specified in paragraph (h)(3) of this section.

1910.119(h)(2)(vi)

The employer shall maintain a contract employee injury and illness log related to the contractor's work in process areas.

1910.119(h)(3)

Contract employer responsibilities.

1910.119(h)(3)(i)

The contract employer shall assure that each contract employee is trained in the work practices necessary to safely perform his/her job.

1910.119(h)(3)(ii)

The contract employer shall assure that each contract employee is instructed in the known potential fire, explosion, or toxic release hazards related to his/her job and the process, and the applicable provisions of the emergency action plan.

1910.119(h)(3)(iii)

The contract employer shall document that each contract employee has received and understood the training required by this paragraph. The contract employer shall prepare a record which contains the identity of the contract employee, the date of training, and the means used to verify that the employee understood the training.

The contract employer shall a	assure that each contract employee follows the safety rules of the facility including the safe work practices required by paragraph
(f)(4) of this section.	
.910.119(h)(3)(v)	
	advise the employer of any unique hazards presented by the contract employer's work, or of any hazards found by the contract

1910.119(i)

Pre-startup safety review.

1910.119(i)(1)

The employer shall perform a pre-startup safety review for new facilities and for modified facilities when the modification is significant enough to require a change in the process safety information.

1910.119(i)(2)

The pre-startup safety review shall confirm that prior to the introduction of highly hazardous chemicals to a process:

1910.119(i)(2)(i)

Construction and equipment is in accordance with design specifications;

1910.119(i)(2)(ii)

Safety, operating, maintenance, and emergency procedures are in place and are adequate;

1910.119(i)(2)(iii)

For new facilities, a process hazard analysis has been performed and recommendations have been resolved or implemented before startup; and modified facilities meet the requirements contained in management of change, paragraph (I).

1910.119(i)(2)(iv)

Training of each employee involved in operating a process has been completed.

1910.119(j)

Mechanical integrity.

1910.119(j)(1)

Application. Paragraphs (j)(2) through (j)(6) of this section apply to the following process equipment:

1910.119(j)(1)(i)

Pressure vessels and storage tanks;

1910.119(j)(1)(ii)

Piping systems (including piping components such as valves);

1910.119(j)(1)(iii)

Relief and vent systems and devices;

1910.119(j)(1)(iv)

Emergency shutdown systems;

1910.119(j)(1)(v)

Controls (including monitoring devices and sensors, alarms, and interlocks) and,

1910.119(j)(1)(vi)

Pumps.

1910.119(j)(2)

Written procedures. The employer shall establish and implement written procedures to maintain the on-going integrity of process equipment.

1910.119(j)(3)

Training for process maintenance activities. The employer shall train each employee involved in maintaining the on-going integrity of process equipment in an overview of that process and its hazards and in the procedures applicable to the employee's job tasks to assure that the employee can perform the job tasks in a safe manner.

1910.119(j)(4)

Inspection and testing.

1910.119(j)(4)(i)

Inspections and tests shall be performed on process equipment.

1910.119(j)(4)(ii)

Inspection and testing procedures shall follow recognized and generally accepted good engineering practices.

1910.119(j)(4)(iii)

The frequency of inspections and tests of process equipment shall be consistent with applicable manufacturers' recommendations and good engineering practices, and more frequently if determined to be necessary by prior operating experience.

1910.119(j)(4)(iv)

The employer shall document each inspection and test that has been performed on process equipment. The documentation shall identify the date of the inspection or test, the name of the person who performed the inspection or test, the serial number or other identifier of the equipment on which the inspection or test was performed, a description of the inspection or test performed, and the results of the inspection or test.

1910.119(j)(5)

Equipment deficiencies. The employer shall correct deficiencies in equipment that are outside acceptable limits (defined by the process safety information in paragraph (d) of this section) before further use or in a safe and timely manner when necessary means are taken to assure safe operation.

1910.119(j)(6)

Quality assurance.

1910.119(j)(6)(i)

In the construction of new plants and equipment, the employer shall assure that equipment as it is fabricated is suitable for the process application for which they will be used.

1910.119(j)(6)(ii)

Appropriate checks and inspections shall be performed to assure that equipment is installed properly and consistent with design specifications and the manufacturer's instructions.

1910.119(j)(6)(iii)

The employer shall assure that maintenance materials, spare parts and equipment are suitable for the process application for which they will be used.

1910.119(k)

Hot work permit.

1910.119(k)(1)

The employer shall issue a hot work permit for hot work operations conducted on or near a covered process.

1910.119(k)(2)

The permit shall document that the fire prevention and protection requirements in 29 CFR 1910.252(a) have been implemented prior to beginning the hot work operations; it shall indicate the date(s) authorized for hot work; and identify the object on which hot work is to be performed. The permit shall be kept on file until completion of the hot work operations.

1910.119(I)

Management of change.

1910.119(I)(1)

The employer shall establish and implement written procedures to manage changes (except for "replacements in kind") to process chemicals, technology, equipment, and procedures; and, changes to facilities that affect a covered process.

1910.119(I)(2)

The procedures shall assure that the following considerations are addressed prior to any change:

1910.119(I)(2)(i)

The technical basis for the proposed change;

1910.119(I)(2)(ii)

Impact of change on safety and health;

1910.119(I)(2)(iii)

Modifications to operating procedures;

1910.119(I)(2)(iv)

Necessary time period for the change; and,

1910.119(I)(2)(v)

Authorization requirements for the proposed change.

1910.119(I)(3)

Employees involved in operating a process and maintenance and contract employees whose job tasks will be affected by a change in the process shall be informed of, and trained in, the change prior to start-up of the process or affected part of the process.

1910.119(1)(4)

If a change covered by this paragraph results in a change in the process safety information required by paragraph (d) of this section, such information shall be updated accordingly.

1910.119(I)(5)

If a change covered by this paragraph results in a change in the operating procedures or practices required by paragraph (f) of this section, such procedures or practices shall be updated accordingly.

1910.119(m)

Incident investigation.

1910.119(m)(1)

The employer shall investigate each incident which resulted in, or could reasonably have resulted in a catastrophic release of highly hazardous chemical in the workplace.

1910.119(m)(2)

An incident investigation shall be initiated as promptly as possible, but not later than 48 hours following the incident.

1910.119(m)(3)

An incident investigation team shall be established and consist of at least one person knowledgeable in the process involved, including a contract employee if the incident involved work of the contractor, and other persons with appropriate knowledge and experience to thoroughly investigate and analyze the incident.

1910.119(m)(4)

A report shall be prepared at the conclusion of the investigation which includes at a minimum:

1910.119(m)(4)(i)

Date of incident;

1910.119(m)(4)(ii)

Date investigation began;

1910.119(m)(4)(iii)

A description of the incident;

1910.119(m)(4)(iv)

The factors that contributed to the incident; and,

1910.119(m)(4)(v)

Any recommendations resulting from the investigation.

1910.119(m)(5)

The employer shall establish a system to promptly address and resolve the incident report findings and recommendations. Resolutions and corrective actions shall be documented.

1910.119(m)(6)

The report shall be reviewed with all affected personnel whose job tasks are relevant to the incident findings including contract employees where applicable.

1910.119(m)(7)

Incident investigation reports shall be retained for five years.

1910.119(n)

Emergency planning and response. The employer shall establish and implement an emergency action plan for the entire plant in accordance with the provisions of 29 CFR 1910.38. In addition, the emergency action plan shall include procedures for handling small releases. Employers covered under this standard may also be subject to the hazardous waste and emergency response provisions contained in 29 CFR 1910.120 (a), (p) and (q).

910.119(o)
Compliance Audits.
910.119(o)(1)
Employers shall certify that they have evaluated compliance with the provisions of this section at least every three years to verify that the procedures and
practices developed under the standard are adequate and are being followed.
910.119(o)(2)
The compliance audit shall be conducted by at least one person knowledgeable in the process.
The compliance duality shall be conducted by at least one person knowledgeable in the process.
010 110(-)/2)
910.119(o)(3)
A report of the findings of the audit shall be developed.
910.119(o)(4)
The employer shall promptly determine and document an appropriate response to each of the findings of the compliance audit, and document that
deficiencies have been corrected.
910.119(o)(5)
Employers shall retain the two (2) most recent compliance audit reports.
910.119(p)
Trade secrets.
910.119(p)(1)
Employers shall make all information necessary to comply with the section available to those persons responsible for compiling the process safety information
(required by paragraph (d) of this section), those assisting in the development of the process hazard analysis (required by paragraph (e) of this section),
those responsible for developing the operating procedures (required by paragraph (f) of this section), and those involved in incident investigations (required by paragraph (f) of this section).
by paragraph (m) of this section), emergency planning and response (paragraph (n) of this section) and compliance audits (paragraph (o) of this section)
without regard to possible trade secret status of such information.
without regard to possible trade secret status or such information.
010 110(-)/2)
910.119(p)(2) Nothing in this paragraph shall produce the ampleyor from requiring the paragraph to whom the information is made available under paragraph (p)(1) of this
Nothing in this paragraph shall preclude the employer from requiring the persons to whom the information is made available under paragraph (p)(1) of this
section to enter into confidentiality agreements not to disclose the information as set forth in 29 CFR 1910.1200.
910.119(p)(3)
Subject to the rules and procedures set forth in 29 CFR 1910.1200(i)(1) through 1910.1200(i)(12), employees and their designated representatives shall have
access to trade secret information contained within the process hazard analysis and other documents required to be developed by this standard.
[57 FR 23060, June 1, 1992; 61 FR 9227, March 7, 1996; 77 FR 17776, March 26, 2012; 78 FR 9313, Feb. 8, 2013]

Freedom of Information Act | Privacy & Security Statement | Disclaimers | Important Web Site Notices | International | Contact Us

U.S. Department of Labor | Occupational Safety & Health Administration | 200 Constitution Ave., NW, Washington, DC 20210

Telephone: 800-321-OSHA (6742) | TTY

www.OSHA.gov

Next Standard (1910.119 App A)

♦ Regulations (Standards - 29 CFR) - Table of Contents